

Sustainably Harvested—Walnut

Pioneer millworks
RECLAIMED & SUSTAINABLE WOOD PRODUCTS



Sourced from forests which are carefully managed according to strict Forest Stewardship Council® (FSC®) requirements, this high-grade Walnut offers a more uniform appearance than its reclaimed counterpart. Expect consistent color tones ranging from brown to purple and a few small knots. This sustainably harvested wood pairs especially well with our custom eco-friendly finishes for floors and paneling.



Pioneer Millworks Sustainably Harvested—Walnut

81027E

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29—Wood strip and plank flooring

06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks
1180 Commercial Drive
Farmington, NY 14425
Phone: 800-951-9663

Pioneer Millworks
2609 SE 6th Avenue
Portland, OR 97202
Phone: 503-719-4800

MATERIALS

1. **Product Name:** Sustainably Harvested Walnut
2. **Species/Description:** Domestic Walnut, smooth planed
3. **Source:** Sustainably Harvested Forests
4. **Color:** Tones may range from brown to purple.
Unlimited color variation is inherent to the product.
5. **Grade:** Select and Better
6. **Dimensions:**
 - Solid**
 - TH—N.A.
 - WD—N.A.
 - LG—N.A.
 - Engineered**
 - TH— $\frac{1}{2}$ " or $\frac{5}{8}$ " as specified
 - WD—4" to 8" as specified
 - LG—12" to 96" random
7. **Milling:** Tongue and Groove Square Edge (TGSQE)
8. **Finish:** Unfinished unless specified otherwise
9. **Hardness:** 1320
(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)
10. **FSC Claim:** (SCS-COC-003998)
 - Solid: N.A.
 - Engineered: FSC Mix 70%

ADDITIONAL INFORMATION

Heartwood: 75% Heartwood

Grain: Clear

Knots: 90% free of knots. Existing knots to be no larger than $\frac{1}{4}$ " diameter.

Texture: Surface should be 100% clear of saw marks.

Voids: No voids are permitted.

Discoloration: Limited mineral staining is permitted.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.

Substrate: FSC Baltic Birch CPCP grade

9mm thickness for finished $\frac{1}{2}$ "

12mm thickness for finished $\frac{5}{8}$ "

No Urea Formaldehyde added (Note: wood has trace amounts naturally)

Glue: Formaldehyde-free low VOC glue

Moisture Content: Kiln dried 6–9% prior to milling.

LEED INFORMATION

MRc3: N.A.

MRc4: N.A.

MRc5: Regional Materials (call for details)

MRc7: Certified Wood—Materials are FSC Mix 70%

RECOMMENDED OVERAGE

Recommend 7–12% additional material for on-site grading, trimming and installation factors.



Information is deemed reliable but subject to change. All photos for representation only. Additional information available at our website or call our wood design experts.