



photo for representation only

## Black & Tan **Reclaimed Oak**

### **Density**

No limitation on grain density

### **Hardness**

1290

### **Heartwood**

Unlimited combination of heartwood and sapwood

### **Grain**

Unlimited mixture of grain patterns

### **Color**

Warm golds and tans combined with as-found surfaces ranging from silver-grey to black with occasional dark grey/black boards, including large areas of original paint.

### **Knots**

Unlimited sound, tight knots permitted, some surface defect from chipped/open knots

### **Texture**

Face of material will have varying textures ranging from rough-sawn or planed, to heavily weathered.

### **Holes**

Nail, knot, and bolt holes may be present and can occasionally reach 1" diameter

### **Discoloration**

Ferrous staining may be present. Color and patina will vary

### **Checks**

Checks allowed as long as the board will hold together for installation.

### **Moisture Content**

Kiln dried to 6 – 9% unless otherwise requested

### **Finish**

Standard product is supplied unfinished

## **Certifications**

### **FSC**

FSC Recycled 100% credit

### **LEED**

MR 4.1 & 4.2 (Material Reuse)

MR 5.1 & 5.2 (Materials)

\* Grading applies to flooring and boardstock, all material graded best face.

1180 Commercial Drive | Farmington, NY 14425 | Tel: 800.951.9663 | Fax: 585.924.9962 [pionermillworks.com](http://pionermillworks.com)