



photo for representation only

## American Gothic **Reclaimed Cherry**

### Density

No limit on grain density

### Hardness

950

### Heartwood

No limit on combination of heartwood and sapwood

### Grain

A mixture of flat sawn and vertical grain

### Color

No restriction on natural color variation. Some variation may be dramatic between heartwood and sapwood

### Knots

No limitation on sound knots. Surface defects resulting from chipped or broken knots will be present

### Texture

Re-sawing and milling removes all but infrequent saw marks and previous wear patterns. Very occasional overwood from natural variation in surface is possible.

### Holes

Nail and other mechanical holes can be present and occasionally reach 3/8" in diameter. Surface defects from insect tracks and pin holes will be present at times in heavy concentrations.

### Discoloration

Ferrous staining from previous fasteners may be present.

### Checks

Checks and crack allowed to 3/32" in widths less than 7". In widths 7" and wider these sizes increase.

### Moisture Content

Kiln dried to 6 – 9% unless otherwise requested

### Finish

Standard product is supplied unfinished

## Certifications



The mark of responsible forestry

### FSC

FSC Recycled 100% credit  
Pioneer Millworks Chain of Custody #: SCS-COC-003998

### LEED

MR 4.1 & 4.2 (Material Reuse)  
MR 5.1 & 5.2 (Materials)

\* Grading applies to flooring and boardstock, all material graded best face.