



photo for representation only

## D-Select **Reclaimed Douglas Fir**

### **Density**

75% dense grain (8 rings or more per inch)

### **Hardness**

660

### **Heartwood**

75% or more heartwood content

### **Grain**

No restriction on grain orientation. Mix of vertical grain and flat sawn

### **Color**

Natural variation in color from heartwood, sapwood, and lighter/darker wood

### **Knots**

In boards less than 5" wide, approx. 50% are clear boards, the remaining 50% are limited to an average of one knot every 4' and wider the length of the board. Boards 5" and wider are limited to an average of one knot every 3' over the length of the board.

### **Texture**

Re-sawing and milling removes all but very infrequent saw marks and previous wear patterns

### **Holes**

Occasional nail holes limited to 3/16" diameter

### **Discoloration**

Limited ferrous staining primarily concentrated around fastener holes

### **Checks**

No shake or structural checks

### **Moisture Content**

Kiln dried to 6 – 9% unless otherwise requested

### **Finish**

Standard product is supplied unfinished

## **Certifications**



The mark of responsible forestry

### **FSC**

FSC Recycled 100% credit  
Pioneer Millworks Chain of Custody #: SCS-COC-003998

### **LEED**

MR 4.1 & 4.2 (Material Reuse)  
MR 5.1 & 5.2 (Materials)

\* Grading applies to flooring and boardstock, all material graded best face.