



photo for representation only

## D-Select Vertical Grain **Reclaimed Douglas Fir**

### Density

75% dense grain (8 rings or more per inch)

### Hardness

660

### Heartwood

75% or more heartwood content

### Grain

100% of face is vertical grain in boards less than 5" and 75% in boards 5" and wider

### Color

Natural Douglas Fir color variation

### Knots

In boards less than 5" wide, approx. 50% are clear boards, the remaining 50% are limited to an average of one knot every 4' over the length of the board. Boards 5" and wider are limited to an average of one knot every 3' over the length of the board.

### Texture

Re-sawing and milling removes all but very infrequent saw marks and previous wear patterns

### Holes

Occasional nail holes limited to 3/16" diameter

### Discoloration

Limited ferrous staining primarily concentrated around fastener holes

### Checks

No shake or structural checks

### Moisture Content

Kiln dried to 6 – 9% unless otherwise requested

### Finish

Standard product is supplied unfinished

## Certifications



The mark of responsible forestry

### FSC

FSC Recycled 100% credit  
Pioneer Millworks Chain of Custody #: SCS-COC-003998

### LEED

MR 4.1 & 4.2 (Material Reuse)  
MR 5.1 & 5.2 (Materials)

\* Grading applies to flooring and boardstock, all material graded best face.