



photo for representation only

## Original **Gym Flooring**

### **Density**

No limit on grain density

### **Hardness**

1450

### **Heartwood**

No limit on combination of heartwood and sapwood

### **Grain**

A mixture of grain orientations

### **Color**

No restriction on natural color variation. Original accent paint in a variety of colors and concentrations will be present.

### **Knots**

Infrequent sound knots may occur

### **Texture**

Areas of peeling or flaking finish will occur as well as occasional previous wear patterns. Expect gaps and overwood once installed.

### **Holes**

Nail and other mechanical holes can be present and occasionally reach 3/8" in diameter. Surface defects from pin holes may occur

### **Discoloration**

Ferrous staining from previous fasteners may be present

### **Checks**

Checks and crack allowed to 3/32" in widths less than 7"

### **Moisture Content**

Kiln dried to 6 – 9% unless otherwise requested

### **Finish**

Standard product is supplied with the original finish and t&g

## **Certifications**



The mark of responsible forestry

### **FSC**

FSC Recycled 100% credit  
Pioneer Millworks Chain of Custody #: SCS-COC-003998

### **LEED**

MR 4.1 & 4.2 (Material Reuse)  
MR 5.1 & 5.2 (Materials)

\* Grading applies to flooring and boardstock, all material graded best face.