



photo for representation only

## Rail Yard Patina **Reclaimed Mixed Oak**

Species note — This typically includes a mix of Red and White Oak in combination and can include other hardwoods from time to time (up to 40%)

### Density

No limit on grain density

### Hardness

1290

### Widths

Random 3 to 5 inch. Widths will be ripped to ¼" increments. No more than three widths will be included per order.

### Lengths

Random 18" – 10'

### Color

A range of grey/brown colors and patinas included

### Knots

No limitation on sound knots. Surface defects from unsound knots may be present

### Texture

Rail Yard Oak is reclaimed from a combination of boards and timbers from the transportation industry. This mixture often shows varied wear patterns, fastener marks, textures. Overwood up to 1/8" can be expected.

### Holes

Infrequent nail holes may be present

### Discoloration

Ferrous staining from previous fasteners or straps may be present

### Checks

Structural checks not affecting the integrity of the plank once installed are allowed, and more prevalent as the width of the material increases

### Moisture Content

Kiln dried to 6 – 9% unless otherwise requested

### Finish

Standard product is supplied unfinished

## Certifications



The mark of responsible forestry

### FSC

FSC Recycled 100% credit  
Pioneer Millworks Chain of Custody #: SCS-COC-003998

### LEED

MR 4.1 & 4.2 (Material Reuse)  
MR 5.1 & 5.2 (Materials)

\* Grading applies to flooring and boardstock, all material graded best face. REV#PMW09112014