Engineered Wood Products



Can a sustainably harvested or reclaimed engineered wood floor be eco-friendly and socially responsible? We studied, researched, and developed until we created our own engineered wood products that are FSC-certified, formaldehyde-free, low-VOC, CARB2, and made right here in the USA.

Available for most of our reclaimed wood and all sustainably harvested species you can mix engineered products into your project while maintaining consistency with your solid wood choices. It comes in two thicknesses, both ready for installation on cement slabs, in basements, over radiant heat, or anywhere you need your floor to have minimal movement.



Pioneer Millworks **Engineered Wood Products**

MANUFACTURER

Pioneer Millworks 1180 Commercial Drive Farmington, NY 14425 Phone: 800-951-9663

Pioneer Millworks 2609 SE 6th Avenue Portland, OR 97202 Phone: 503-719-4800

SPECIES/GRADES AVAILABLE:

Reclaimed:

American Gothic: Ash, Chestnut, Elm, Hickory, Mixed Hardwoods, Mixed Oak, Walnut, White Oak

Settlers' Plank: Chestnut, Mixed Hardwoods, Mixed Oak

Heart Pine (All grades)

Sustainably Harvested: White Oak, Ash, Maple, Hickory, Walnut

SIZE:

Lengths:

12"-94", random

Widths:

4"-9" (nominal), random Special orders available

Thickness:

5/8" 1/2"

ADDITIONAL INFORMATION:

Wear Layer:

3/16" wear layer

100% reclaimed or sustainably harvested wood

Substrate: FSC Baltic Birch

9mm (7 ply) thickness for finished 1/2" 12mm (9 ply) thickness for finished 5/8"

CARB2 and TOSCA compliant Glue: Formaldehyde-free, low-VOC glue

Milling: T&G, end matched, square edge—microbevel as requested

Finishes: Available finished or unfinished

Moisture Content: Kiln dried 6-9% prior to milling

Crafted in the USA: Reclaimed and manufactured in the USA

LEED INFORMATION

MRc3*: Materials Reuse

(materials used for this credit cannot be applied to MRc4 or MRc5) MRc4*: Recycled Content, 100% Post-Consumer Recycled Content (materials used for this credit cannot be applied to MRc3 or MRc7)

MRc5: Regional Materials (call for details)

MRc7: Engineered FSC Mix

RECOMMENDED OVERAGE

Recommend 7-12% additional material for on-site grading, trimming and installation factors. (For custom projects, consider 15%.)

















Information is deemed reliable but subject to change, All photos for representation only. Additional information available at our website or call our wood design experts.