

# Modern Farmhouse—White Oak, Casual




Pioneer Millworks  
RECLAIMED & SUSTAINABLE WOOD PRODUCTS

Naked



Modern Farmhouse is a more casual grade of oak flooring which pairs casual live-sawn grain and knots with contemporary color and finishing preferences. Preserving sound knots and accepting a mix of grain orientations allows us to make the most of each board, reducing waste and achieving an appearance that is true to the tree. The classic fresh-sawn white oak color tone acts as a neutral base for both a range of Scandinavian whites and modern black finishes. Or choose a “naked” finish which has commercial grade protection and wear resistance but the look and touch of raw unfinished wood. This collection is LEED-point eligible and sourced from FSC-certified® forests.


## Finish Color Options:




Espresso




White Wash



Linen



Straw



Pure

# Pioneer Millworks

## Modern Farmhouse—White Oak, Casual

12/2018

### CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29—Wood Strip and Plank Flooring  
06 42 00—Wood Paneling

### MANUFACTURER

Pioneer Millworks  
1180 Commercial Drive  
Farmington, NY 14425  
Phone: 800-951-9663

Pioneer Millworks  
2609 SE 6th Avenue  
Portland, OR 97202  
Phone: 503-719-4800

### MATERIALS

1. **Product Name:** Modern Farmhouse White Oak, Casual
2. **Species/Description:** Domestic White Oak, smooth planed
3. **Source:** Sustainably Harvested Forests
4. **Color:** Tones may range from cream to brown. Unlimited color variation is inherent to the product.
5. **Grade:** Casual
6. **Dimensions:**
  - Solid**  
TH—N/A  
WD—N/A  
LG—N/A
  - Engineered**  
TH—5/8"  
WD—4" to 9" as specified.  
LG—12" to 96" random
7. **Milling:** Unfinished: Tongue and Groove Square Edge (TGSQE), Prefinished: Tongue and Groove Micro Bevel Edge (TGMBVE)
8. **Finish:** Unfinished unless specified otherwise
9. **Hardness:** 1260  
(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)
10. **FSC Claim:** (SCS-COC-003998)  
**Engineered:** FSC Mix

### ADDITIONAL INFORMATION

**Heartwood:** No limitation on heartwood.

**Grain:** No limitation on grain orientation.

**Knots:** No limitation on sound knots.

**Texture:** Surface should be 100% clear of saw marks.

**Voids:** Chipped or open knots can be present and occasionally reach up to 1/2" diameter in solid and engineered flooring so long as the voids do not extend to the edge of the board. Maximum void diameter in solid paneling is 1". Larger voids may occasionally be included to preserve long lengths.

**Discoloration:** Unlimited mineral staining is permitted.

**Checks:** Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.

**Moisture Content:** Kiln dried 6–9% prior to milling.

### LEED INFORMATION

**MRC3:** N.A.

**MRC4:** N.A.

**MRC5:** Regional Materials (call for details)

**MRC7:** Certified Wood—Materials are FSC Mix

### RECOMMENDED OVERAGE

Recommend 7–12% additional material for on-site grading, trimming and installation factors.



The mark of responsible forestry



Information is deemed reliable but subject to change. All photos for representation only. Additional information available at our website or call our wood design experts.