

Larch—Exterior Siding, Standard



Finish Color: Light Brown

Larch exterior shiplap siding is a great choice for those looking for a durable wood siding option that wears similar to cedar. This species is insect-resistant and moderately rot-resistant. It comes standard with a shiplap profile, and can be run either vertically or horizontally; its long lengths allowing for more coverage in one go. Our Standard Larch is harvested from British Columbia as a bi-product of logging. These commodity timbers are smaller, fast-growing and make for another sustainable option in our palette of exterior sidings.

Order it prefinished with a non-VOC water-based penetrating sealer to save time and money on installation. Our natural finish option will highlight the variations and grain of the Larch, or choose one of our color stain options.

Why Larch?

Larch is an underutilized species with rot resistance greater than Douglas fir, an attractive grain, neutral color, and affordability making it an ideal wood for siding products. By keeping this wood out of pulp mills and fireplaces, you are also doing your part to reduce carbon emissions.



Pioneer Millworks

Larch—Exterior Siding, Standard

6/2019

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

07 46 23—Wood Siding
06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks
1180 Commercial Drive
Farmington, NY 14425
Phone: 800-951-9663

Pioneer Millworks
2609 SE 6th Avenue
Portland, OR 97202
Phone: 503-719-4800

MATERIALS

1. **Product Name:** Standard Larch Siding
2. **Species/Description:** Domestic Larch, smooth planed
3. **Source:** Sustainably Harvested Forests
4. **Color:** Tones range from cream to brown. Unlimited color variation is inherent to the product.
5. **Grade:** Standard
6. **Dimensions:**
 - Solid—Shiplap**
TH—5/8"
WD—5" face
LG—4' to 16' random
 - Engineered**
TH—N.A.
WD—N.A.
LG—N.A.
7. **Milling:** Shiplap no reveal (SL)
8. **Finish:** Unfinished or prefinished with a tinted Poly Sealer as specified (2 coats face, one coat back).
9. **Hardness:** 830
(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)
10. **FSC Claim:** None

ADDITIONAL INFORMATION


Heartwood: 75% Heartwood
Grain: No restriction
Knots: Sound tight knots included.
Texture: Surface should be 100% clear of saw marks.
Voids: No voids are permitted.
Discoloration: Limited mineral staining is permitted.
Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.
Moisture Content: Kiln dried 15% prior to milling.

LEED INFORMATION

MRC5: Regional Materials (call for details)

RECOMMENDED OVERAGE

Recommend 7–12% additional material for on-site grading, trimming and installation factors.



Natural



Bronze Cedar




Light Brown



Mahogany



Battleship Grey



Unfinished



Information is deemed reliable but subject to change. All photos for representation only. Additional information available at our website or call our wood design experts.