

# Standard—Larch Siding




Finish Color: Light Brown

Larch exterior shiplap siding is a great choice for those looking for a durable wood siding option that wears similar to cedar. This species is insect-resistant and moderately rot-resistant. It comes standard with a shiplap profile, and can be run either vertically or horizontally; its long lengths allowing for more coverage in one go. Our Standard Larch is harvested from British Columbia as a bi-product of logging. These commodity timbers are smaller, fast-growing and make for another sustainable option in our palette of exterior sidings.

Order it prefinished with a non-VOC water-based penetrating sealer to save time and money on installation. Our natural finish option will highlight the variations and grain of the Larch, or choose one of our color stain options.

## Why Larch?

Larch is an underutilized species with rot resistance greater than Douglas fir, an attractive grain, neutral color, and affordability that make it an ideal wood for siding products. Much of the Larch that we use is sourced from “standing dead” trees. Unlike Douglas fir which deteriorates after a mere 18 months after death, these 400-500 year old Larch trees remain remarkably pristine for a much longer time period. These trees yield some spectacularly clear and tight grain boards.



# Pioneer Millworks Standard—Larch Siding

1/2020

## CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

07 46 23—Wood Siding  
06 42 00—Wood Paneling

## MANUFACTURER

Pioneer Millworks  
1180 Commercial Drive  
Farmington, NY 14425  
Phone: 800-951-9663

Pioneer Millworks  
2609 SE 6th Avenue  
Portland, OR 97202  
Phone: 503-719-4800

## MATERIALS

1. **Product Name:** Standard Larch Siding
2. **Species/Description:** Western Larch, smooth planed
3. **Source:** Sustainably Harvested Forests
4. **Color:** Tones range from cream to brown. Unlimited color variation is inherent to the product.
5. **Grade:** Standard
6. **Dimensions:**
  - Solid—Shiplap**  
TH—5/8"  
WD—5" face  
LG—4' to 16' random
  - Engineered**  
TH—N.A.  
WD—N.A.  
LG—N.A.
7. **Milling:** Shiplap no reveal (SL)
8. **Finish:** Unfinished or prefinished with a tinted Poly Sealer as specified (2 coats face, one coat back).
9. **Hardness:** 830  
(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)
10. **FSC Claim:** None

## ADDITIONAL INFORMATION

**Heartwood:** 75% Heartwood  
**Grain:** No restriction  
**Knots:** Sound tight knots included.  
**Texture:** Surface should be 100% clear of saw marks.  
**Voids:** No voids are permitted.  
**Discoloration:** Limited mineral staining is permitted.  
**Checks:** Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.  
**Moisture Content:** Kiln dried 15% prior to milling.

## LEED INFORMATION

**Mrc5:** Regional Materials (call for details)

## RECOMMENDED OVERAGE

Recommend 7–12% additional material for on-site grading, trimming and installation factors.



Natural




Bronze Cedar



Light Brown



Mahogany



Battleship Grey



Unfinished



Information is deemed reliable but subject to change. All photos for representation only. Additional information available at our website or call our wood design experts.