

The Natural Expressions Collection: Casual White Oak



Made with our sustainably harvested FSC® Certified Casual White Oak, the Natural Expressions Collection utilizes an 8" wide plank format and an all-natural UV Cured Hard-Wax oil finish, giving any space an organic flow by allowing each board to express a variety of wood grain patterns.

Developed in collaboration with celebrated interior designer David Senise, this collection combines elements inspired by nature to bring thoughtful sophistication & grounded aesthetics from the natural world into commercial & residential spaces.



Shoji White



Hazelwood



Ginger Root



Toasted Wheat



Autumn Brown



Coffee Bean



Warm Umber




Royal Acorn



Driftwood



Nantucket Fog



Rain Cloud



Osaka Black

Pioneer Millworks

The Natural Expressions Collection: Casual White Oak

8/2023

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29—Wood Strip and Plank Flooring
06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks East
1180 Commercial Drive
Farmington, NY 14425
Phone: 800-951-9663

MATERIALS

1. **Product Name:** The Natural Expressions Collection: Casual White Oak
2. **Species/Description:** Domestic White Oak, smooth planed
3. **Source:** Sustainably Harvested Forests
4. **Color:** Available in a range of finishes by inspired by Nature
5. **Grade:** Casual
6. **Dimensions:**
 - Engineered**
 - TH—5/8"
 - WD—8"
 - LG—18" to 12' random
7. **Milling:**
 - Prefinished: Tongue and Groove Micro Bevel Edge (TGMBVE)
8. **Finish:** UV Cured Hard-Wax Oil
9. **Hardness:** 1260
 - (Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)
10. **FSC Claim:** None

ADDITIONAL INFORMATION

Heartwood: No limitation on heartwood.

Grain: No limitation on grain orientation.

Knots: No limitation on sound knots.

Texture: Surface should be 100% clear of saw marks.

Voids: Chipped or open knots can be present and occasionally reach up to 1/2" diameter so long as the voids do not extend to the edge of the board. Larger voids may occasionally be included to preserve long lengths. Most voids will be filled prior to finishing.

Discoloration: Unlimited mineral staining is permitted.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.

Moisture Content: Kiln dried 6–9% prior to milling.

LEED INFORMATION

MRC3: N.A.

MRC4: N.A.

MRC5: Regional Materials (call for details)

RECOMMENDED OVERAGE

Recommend 7–12% additional material for on-site grading, trimming and installation factors.



Information is deemed reliable but subject to change. All photos for representation only. Additional information available at our website or call our wood design experts.