

Modern Farmhouse Casual White Oak



Pioneer Millworks
RECLAIMED & SUSTAINABLE WOOD PRODUCTS



Our Modern Farmhouse Casual White Oak makes the most of live sawn boards, preserving sound knots and embracing color variation. Made with FSC Mix Certified lumber, this grade maximizes the yield of each log and is true to the organic nature of the tree in terms of appearance. Colors range from tan to brown.



Pioneer Millworks

Modern Farmhouse Casual White Oak

10/24

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29—Wood Strip and Plank Flooring

06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks East
1180 Commercial Drive
Farmington, NY 14425
Phone: 800-951-9663

Pioneer Millworks West
2655 NE Orchard Ave.
McMinnville, OR 97128
Phone: 503-437-9017

MATERIALS

Product Name: Modern Farmhouse Casual White Oak

Species/Description: Domestic White Oak, smooth planed

Source: Sustainably Harvested Forests

Color: Tones may range from cream to brown. Unlimited color variation is inherent to the product.

Grade: Casual

Dimensions:

Solid

TH—3/4"

WD—6" or 7" as specified, wider widths may be available upon request

LG—18" to 12' random

Engineered

TH—5/8"

WD—6" or 7" as specified, wider widths may be available upon request

LG—18" to 12' random

Milling:

Unfinished: Tongue and Groove Square Edge (TGSQE),


Prefinished: Tongue and Groove Micro Bevel Edge (TGMBVE)

Finish: Unfinished unless specified otherwise.

Hardness: 1260

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

FSC Claim: (SCS-COC-003998)



ADDITIONAL INFORMATION

Heartwood: No limitation on heartwood.

Grain: No limitation on grain orientation.

Knots: No limitation on sound knots.

Texture: Surface should be 100% clear of saw marks.

Voids: Chipped or open knots can be present and occasionally reach up to 1/2" diameter so long as the voids do not extend to the edge of the board.

Larger voids may occasionally be included to preserve long lengths.

Discoloration: Unlimited mineral staining is permitted.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.

Moisture Content: Kiln dried 6–9% prior to milling.

LEED INFORMATION

MRC5: Regional Materials (call for details)

MRC7: Certified Wood—Materials are FSC Mix

EQ Credit: Greenguard Gold

RECOMMENDED OVERAGE

Recommend 7–12% additional material for on-site grading, trimming and installation factors.



The mark of responsible forestry



Information is deemed reliable but subject to change. All photos for representation only. Additional information available at our website or call our wood design experts.