

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

- 09 64 20 — Reclaimed Wood Flooring
- 09 64 30 — Engineered Wood Flooring
- 06 42 00 — Wood Paneling

MANUFACTURER

Pioneer Millworks
 1180 Commercial Dr
 Farmington, NY 14425

MATERIALS

Product: American Gothic White Oak
Collection: Reclaimed
Species: Domestic White Oak
Core: 9-Ply FSC® Certified & TCSA Compliant Birch Plywood
Texture: Smooth Planed
Source: Agricultural Deconstruction
Color: Tones may range from tan to brown.

Unlimited color variation is inherent to the product.

Finish: Available in Naked and Pure

Hardness: 1360

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

ADDITIONAL INFORMATION

Heartwood: No Restriction
Grain: No Restriction
Knots: No limitations on sound knots.
Surface defects from chipped or open knots may be present.

Texture: Surface should generally be 95% clear of saw marks or patina.

Voids: In engineered prefinished product Voids up to 1" in diameter will be filled with a black composite.

Insect marks, including pinholes, may also be present on the surface.

Discoloration: Ferrous staining from previous fasteners may be present.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.

Moisture Content: Kiln dried 6–9% prior to milling.

CERTIFICATIONS & LEED INFORMATION

FSC® Claim: SCS-COC-003998-D

Engineered	Solid
FSC® Mix	FSC® Recycled 100%
Greenguard GOLD Certified	

MRC3: Materials Reuse

(materials used for this credit cannot be applied to MRC4 or MRC5)

MRC4: Recycled Content, 100% Post-Consumer Recycled Content

(materials used for this credit cannot be applied to MRC3 or MRC7)

MRC5: Regional Materials (call for details)

INSTALLATION RECOMMENDATIONS

Overage: Minimum 10% additional material

for on-site grading, trimming and installation factors.

Climate: As with any wood flooring product, the room temperature should be held at a consistent range between **60-80° F** with relative humidity between **30-60%**.

Environmental conditions consistently outside of these parameters could result in product performance issues.

DIMENSIONS & MILLING

Engineered (Prefinished)

Thickness: 5/8"

Profile + End Match: TGBMVE (Tongue and Groove Micro-Bevel Edge)

Width: 4"– 8" random

Wear Layer: 3/16"

Length: 18"– 12' random

Core: 1/2"

Solid (Unfinished)

Thickness: 3/4"

Profile + End Match: TGSQE (Tongue and Groove Square Edge)

Width: 3"– 5" random
wider widths may be available upon request


Back-Relief: Included

Length: 18"– 12' random


American Gothic White Oak

Coveted for its durability and stunning grain patterns, our reclaimed White Oak is salvaged from agricultural and industrial structures. Tightly grained and featuring warm honey to caramel tones, this quintessential American species has just the right amount of character from its previous life to work perfectly in any setting.

Engineered (Prefinished)



Solid (Unfinished)






Unfinished

SKU# 23112110010



Naked

SKU# 23112110111



Pure

SKU# 23112110211