

Clean White Oak

Sophisticated, warm, and chic this line offers a twist on classically elegant species, matching function with contemporary farmhouse style. Showcasing modern flare with a more uniform appearance than its reclaimed counterpart, this high grade of White Oak is sourced from forests which are carefully managed to strict Forest Stewardship Council® (FSC®®) requirements. Celebrated in natural, fresh-sawn tones, expect consistent hues ranging from cream to tan, relaxed grain patterns, and as a few small knots. This sustainably harvested wood pairs especially well with our custom eco-friendly finishes for flooring and paneling.

Engineered (Prefinished) 5"-7" as specified (nominal) 7/8" TGMBVE + End Match

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29 — Wood strip and plank flooring

09 64 30 — Engineered Wood Flooring

06 42 00 — Wood Paneling

MANUFACTURER

Pioneer Millworks 1180 Commercial Dr Farmington, NY 14425

MATERIALS

Product: Clean White Oak

Collection: Modern Farmhouse

Species: Domestic White Oak

Core: 9-Ply FSC® Certified & TCSA Compliant Birch Plywood

Texture: Smooth Planed Grade: Clean Source: Sustainably Harvested Forests

Color: Tones may range from cream to tan.

Unlimited color variation is inherent to the product.

Finish: Available in Naked, Pure, 5% White, Castle Brown, and Espresso

Hardness: 1360

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

DIMENSIONS & MILLING

Engineered (Prefinished)

		Profile	TGMBVE
Thickness:	5/8"	+ End Match:	(Tongue and Groove Micro-Bevel Edge)

Width 5'' - I'' Wear Layer: 3/16''

Length: 18" – 12' Core: 1/2"

Solid

Available Upon Request

ADDITIONAL INFORMATION

Heartwood: 75% or greater Heartwood

Grain: Clear

Knots: Primarily free of knots.

Existing knots generally do not exceed 1/2" diameter.

Voids: No voids are permitted.

Discoloration: Limited mineral staining is permitted. **Checks:** Only minor surface checking is permitted.

Moisture Content: Kiln dried 6-9% prior to milling.

CERTIFICATIONS & LEED INFORMATION

FSC® Claim: SCS-COC-003998-D

Engineered

FSC® Mix

Greenguard GOLD Certified

MRc5: Regional Materials (call for details)

INSTALLATION RECOMMENDATIONS

Overage: Minimum 10% additional material

for on-site grading, trimming and installation factors.

Climate: As with any wood flooring product, the room temperature should be held at a consistent range between 60-80° F with relative humidity between 30-60%.

Environmental conditions consistently outside of these parameters could result in product performance issues.







Unfinished SKU# 22182110010

Naked SKU# 22182110111







Espresso SKU# 22182111111 Castle Brown SKU# 22182111211

FSC* A000521