



Clean Walnut

Sophisticated, warm, and chic this line offers a twist on classically elegant species, matching function with contemporary farmhouse style. Showcasing modern flare with a more uniform appearance than its reclaimed counterpart, this high grade of Walnut is sourced from carefully managed forests. Celebrated in natural, fresh-sawn tones, expect consistent hues ranging from brown to purple, relaxed grain patterns, and a few small knots. This sustainably harvested wood pairs especially well with our custom eco-friendly finishes for flooring and paneling.

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

- 09 64 29 — Wood strip and plank flooring
- 09 64 30 — Engineered Wood Flooring
- 06 42 00 — Wood Paneling

MANUFACTURER

Pioneer Millworks
1180 Commercial Dr
Farmington, NY 14425

MATERIALS

- Product: Clean Walnut
- Collection: Modern Farmhouse
- Species: Domestic Walnut
- Core: 9-Ply FSC® Certified & TCSA Compliant Birch Plywood
- Texture: Smooth Planed Grade: Clean
- Source: Sustainably Harvested Forests
- Color: Tones may range from brown to purple.

Unlimited color variation is inherent to the product.

Finish: Available in Unfinished, Naked, and Pure

Hardness: 1010

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

ADDITIONAL INFORMATION

Heartwood: 75% or greater Heartwood

Grain: Clear

Knots: Primarily free of knots.

Existing knots generally do not exceed 12" in diameter.

Voids: No voids are permitted.

Discoloration: Limited mineral staining is permitted.

Checks: Only minor surface checking is permitted.

Moisture Content: Kiln dried 6–9% prior to milling.

CERTIFICATIONS & LEED INFORMATION

FSC® Claim: None

Greenguard GOLD Certified

MRC5: Regional Materials (call for details)

INSTALLATION RECOMMENDATIONS

Overage: Minimum 10% additional material

for on-site grading, trimming and installation factors.

Climate: As with any wood flooring product, the room temperature should be held at a consistent range between **60-80° F** with relative humidity between **30-60%.**


Environmental conditions consistently outside of these parameters could result in product performance issues.

DIMENSIONS & MILLING

Engineered (Prefinished)

Thickness:	5/8"	Profile + End Match:	TGMBVE (Tongue and Groove Micro-Bevel Edge)
Width:	4" - 6" as specified (nominal)	Wear Layer:	3/16"
Length:	18" - 12' random	Core:	1/2"

Engineered (Prefinished)





Unfinished

SKU# 22182010010



Naked

SKU# 22182010111



Pure

SKU# 22182010211