


Black & Tan

This reclaimed mix of Domestic Oak features hints of its original non-toxic black paint from its previous life as horse farm fencing deep in the grain and fissures of the smooth planed surface. An exciting blend of warm tones with varying lights and darks, you'll find occasional knots and a modest price point on these single width reclaimed planks.



CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 20 — Reclaimed Wood Flooring

06 42 00 — Wood Paneling

MANUFACTURER

Pioneer Millworks 1180 Commercial Dr Farmington, NY 14425

MATERIALS

Product: Black & Tan Reclaimed Oak

Collection: Reclaimed
Species: Reclaimed Oak
Texture: Smooth Planed

Source: Agricultural Deconstruction

Color: Tones may range from tan to pink.

Unlimited color variation is inherent to the product.

Finish: Unfinished

Hardness: 1290 - 1360

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

DIMENSIONS & MILLING

Solid (Unfinished)

Thickness: 3/4" Profile (Tongue and Groove Square Edge)

Width: 3 3/4" Back-Relief: Included

Length: 12"- 6.5'

ADDITIONAL INFORMATION

Heartwood: No Restriction

Grain: No Restriction

Knots: No limitations on sound knots.

Surface defects from chipped or open knots may be present.

Texture: Surface should generally be 95% clear of saw marks or patina.

Voids: Nail holes and open knots can be present and may reach 1/2" in dameter. Larger voids may be included in longer planks.

Insect marks, including pinholes, may also be present on the surface.

Discoloration: Ferrous staining from previous fasteners may be present.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.

Moisture Content: Kiln dried 6-9% prior to milling.

CERTIFICATIONS & LEED INFORMATION

FSC® Claim: FSC Recycled 100% (GFA-COC-008489)

MRc3: Low-Emmiting Materials (Unfinished Wood)

MRc4: Building Product Selection and Procurement
(FSC Recycled 100%)

INSTALLATION RECOMMENDATIONS

Overage: Minimum 10% additional material for on-site grading, trimming and installation factors.

Climate: As with any wood flooring product, the room temperature should be held at a consistent range between 60-80° F with relative humidity between 30-60%.

Environmental conditions consistently outside of these parameters could result in product performance issues.



Unfinished

SKU# 13121810010