




SKU# 11151010017

## American Prairie Brown Board

Our take on reclaimed barn wood paneling is broad and dynamic in scope, incorporating wood that is salvaged not just from barns but also agricultural fencing and other structures that have endured the elements. Brown Board features rich tones and a variety of original textures: planed, rough sawn, and lightly weathered. Our customers most often use this reclaimed wood for paneling and ceilings, adding special touches to kitchen islands, counters, and custom spaces.



### CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

06 05 55—Reclaimed Wood Products & Materials  
06 42 00—Wood Paneling  
07 46 23—Wood Siding

### MANUFACTURER

Pioneer Millworks 1180 Commercial Dr Farmington, NY 14425

### MATERIALS

**Product:** American Prairie Brown Board  
**Collection:** American Prairie  
**Species:** Reclaimed Mixed Hardwoods and/or Softwoods  
**Texture:** Original Patina  
**Source:** Agricultural/Industrial Deconstruction  
**Color:** Tones may range from tan to brown.  
*Unlimited color variation is inherent to the product.*  
**Finish:** Unfinished unless specified otherwise.  
**Hardness:** 420–1100  
*(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)*

### DIMENSIONS & MILLING

**Profile** S3S (Surfaced 3 sides) R2E (Ripped on two edges)  
**+ End Match:** available upon request  
**Thickness:** 5/8"– 1" variable  
**Width:** 4"– 8" random  
*Wider widths may be available upon request*  
**Length:** 18"– 12' random

### ADDITIONAL INFORMATION

**Heartwood:** No restriction  
**Grain:** No restriction  
**Knots:** No limitations on sound knots.  
*Surface defects from chipped or open knots may be present.*  
**Texture:** This mixture shows a varied pattern of saw marks, wear patterns, colors and textures. Overwood of up to 1/4" can be expected.  
**Voids:** Fastener holes and open knots can be present and may reach 2" in diameter. Larger voids are occasionally included to preserve long lengths.  
*Surface defects from insect marks, including pin holes may be present.*  
**Discoloration:** Ferrous staining from previous fasteners may be present.  
**Checks:** Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.  
**Moisture Content:** Kiln dried 6–9% prior to milling.

### CERTIFICATIONS & LEED INFORMATION

**FSC Claim:** FSC Recycled 100% (GFA-COC-008489)  
**MRc3:** Low-Emitting Materials (Unfinished Wood)  
**MRc4:** Building Product Selection and Procurement  
*(FSC Recycled 100%)*

### INSTALLATION RECOMMENDATIONS

**Overage:** Minimum 15% additional material  
*For on-site grading, trimming and installation factors.*  
**Climate:** As with any wood product, extreme climate conditions including heat, cold, humid or arid can cause movement and performance issues with the material.