



Clear Vat Stock

Salvaged from vinegar vats, this material is primarily made up of Cypress and Douglas fir and is smooth planed, exposing the tight clear grain and the blondish-amber color tones of the wood. Typically, 10–20% of these planks will include some dark staining.

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 20 — Reclaimed Wood Flooring

06 42 00 — Wood Paneling

MANUFACTURER

Pioneer Millworks
1180 Commercial Dr
Farmington, NY 14425

MATERIALS

Product:	Clear Vat Stock
Collection:	Reclaimed
Species:	Primarily Reclaimed Cypress and Douglas Fir
Texture:	Smooth Planed
Source:	Salvaged Vat Stock
Color:	Tones may range from deep brown to charcoal. <i>May include occasional paint, old machine oil stains, and a range of wear marks.</i>
Finish:	Unfinished <i>Available prefinished upon request</i>
Hardness:	660 <i>(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)</i>

DIMENSIONS & MILLING

Profile:	TGMBVE (Tongue and Groove Micro-Bevel Edge)
Thickness:	5/8"
Width:	3"– 8" nominal
Length:	18"– 12' random

ADDITIONAL INFORMATION

Heartwood:	No restriction
Grain:	No restriction
Knots:	Primarily free of knots. <i>Existing knots generally do not exceed 1/2" in diameter.</i>
Discoloration:	Typically, 10–20% of these planks will include some dark staining.
Checks:	Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.
Moisture Content:	Kiln dried 6–9% prior to milling.


CERTIFICATIONS & LEED INFORMATION

FSC Claim:	FSC Recycled 100% (GFA-COC-008489)
MRC4:	Building Product Selection and Procurement <i>(FSC Recycled 100%)</i>

INSTALLATION RECOMMENDATIONS

Overage:	Minimum 10% additional material <i>For on-site grading, trimming and installation factors.</i>
Climate:	As with any wood flooring product, the room temperature should be held at a consistent range between 60-80° F with relative humidity between 30-60% . <i>Environmental conditions consistently outside of these parameters could result in product performance issues.</i>

Solid (Unfinished)



TGMBVE
Non-End Match





Unfinished

SKU# 04474



5% White

SKU# 04908



Espresso

SKU# 04909



Faux Shou Sugi Ban

SKU# 04953