



Wire-Brushed Indonesian Teak

We've searched the globe to bring you environmentally friendly and ethically sourced teak. This extremely versatile species is reclaimed from non-Burmese sources and is socially responsible—additionally, 1% of our teak sales are donated to the Borneo Project in their fight to end the loss of habitat for the indigenous peoples of Indonesia.

Our Wire Brushed grade has a lightly textured surface that gives depth to the swirling tans and toffee browns of the wood. Tight grain makes Teak strong and durable, able to withstand the wear and tear of shoes, animals, and weather. Natural oils make it resistant to rot, insects, and fungi. Thanks to its water-resistant nature, consider including the warm tones and texture of Teak in place of tile in places like kitchens and baths. Add a color finish to customize your hue, use it indoors or outdoors, on vertical or horizontal surfaces—the versatility of teak makes it a valuable arsenal in any design tool-kit.

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 20 — Reclaimed Wood Flooring
09 64 30 — Engineered Wood Flooring
06 42 00 — Wood Paneling

MANUFACTURER

Pioneer Millworks West

2655 NE Orchard Ave
McMinnville, OR 97128

MATERIALS

Product: Wire-Brushed Indonesian Reclaimed Teak

Collection: Reclaimed Indonesian Teak

Species: Reclaimed Indonesian Teak

Core: 3-Ply Solid Core Construction 100% Teak

Texture: Wire-Brushed

Color: Tones may range from golden tan to toffee brown.

Unlimited color variation is inherent to the product.

Grade: Wire-Brushed

Finish: Unfinished or Available in Pure, White Wash, Donovan, Smoke, Straw, Sand Dune, Black Pepper, and Ebony.

** Shown Unfinished*

Hardness: 1070

(Janka Ball Test ASTM D143, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

DIMENSIONS & MILLING

Profile: **TGMBVE** (Tongue and Groove Micro-Bevel Edge)
+ End Match:

Wear Layer: **1/8"**

Thickness: **9/16"**

Width: **3 1/2" or 5 1/4" as specified**

Wider widths may be available upon request

Length: **2'-7" random**

CERTIFICATIONS & LEED INFORMATION

FSC® Claim: FSC Mix Credit (GFA-COC-008489)

MRc4: Building Product Selection and Procurement
(FSC Recycled 100%)

ADDITIONAL INFORMATION

Heartwood: No Restriction

Grain: No Restriction

Knots: No limitations on sound knots.

Surface defects from chipped or open knots may be present.

Voids: Nail, bolt and other mechanical holes can be present and occasionally reach 3/8" in diameter.
Voids up to 2" in diameter may be filled with plugs.

Discoloration: Ferrous staining from previous fasteners may be present.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed.

Moisture Content: Kiln dried 6–9% prior to milling

INSTALLATION RECOMMENDATIONS

Overage: **Minimum 10% additional material for on-site grading, trimming and installation factors.**

Climate: As with any wood flooring or paneling product, the room temperature should be held at a consistent range between 60-80° F with relative humidity between 30-60%.

Environmental conditions consistently outside of these parameters could result in product performance issues.



SKU# 24441910011



SKU# 24441910211



SKU# 24441910611

