


# Clean Ash

Sophisticated, warm, and chic this line offers a twist on classically elegant species, matching function with contemporary farmhouse style. Showcasing modern flare with a more uniform appearance than its reclaimed counterpart, this high grade of Ash is sourced from forests which are carefully managed to strict Forest Stewardship Council® (FSC®) requirements. Celebrated in natural, fresh-sawn tones, expect consistent hues ranging from cream to light brown, relaxed grain patterns, and as a few small knots. This sustainably harvested wood pairs especially well with our custom eco-friendly finishes for flooring and paneling.



# CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29 — Wood strip and plank flooring

09 64 30 — Engineered Wood Flooring

**06 42 00** — Wood Paneling

# **MANUFACTURER**

Pioneer Millworks 1180 Commercial Dr Farmington, NY 14425

### **MATERIALS**

Product: Clean Ash

Collection: Modern Farmhouse Species: Domestic White Ash

Core: 9-Ply FSC® Certified & TCSA Compliant Birch Plywood

Texture: Smooth Planed Grade: Clean Source: Sustainably Harvested Forests

**Color:** Tones may range from cream to brown. *Unlimited color variation is inherent to the product.* 

Finish: Available in Naked, Pure, 5% White, Castle Brown, and Espresso

Hardness: 1320

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

# **DIMENSIONS & MILLING**

Engineered (Prefinished)

Thickness: 5/8" Profile Tongue and Groove Hend Match: Groupe and Groove Micro-Bevel Edge)

Width: 4" - 6" Wear Layer: 3/16"

Length: 18" – 12' Core: 1/2"

# **ADDITIONAL INFORMATION**

Heartwood: 75% or greater Heartwood

Grain: Clear

Knots: Primarily free of knots.

Existing knots generally do not exceed 1/2" in diameter.

Voids: No voids are permitted.

Discoloration: Limited mineral staining is permitted.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent

as the width of the material increases.

Moisture Content: Kiln dried 6–9% prior to milling.

# **CERTIFICATIONS & LEED INFORMATION**

FSC® Claim: FSC Mix Credit (GFA-COC-008489)

**GREENGUARD Gold Certified** 

MRc3: Low-Emmiting Materials (GREENGUARD Gold)

**MRc4:** Building Product Selection and Procurement

(FSC Mix Credit)

#### INSTALLATION RECOMMENDATIONS

Overage: Minimum 10% additional material

for on-site grading, trimming and installation factors.

Climate: As with any wood flooring product, the room temperature should be held at a consistent range between 60-80° F with relative humidity between 30-60%.

Environmental conditions consistently outside of these parameters could result in product performance issues.







GREENGUARD

PRODUCT CERTIFIED FOR
U. COMPAGE, EMISSIONS
U. 2818

GOLD

FSC\*
C217480





SKU# 22181211011

5% White