


The Natural Expressions Collection

FLOORING DESIGNED WITH DAVID SENISE

Made with our sustainably harvested FSC® Certified Casual White Oak, the Natural Expressions Collection utilizes an 8" wide plank format and an all-natural UV Cured Hard-Wax oil finish, giving any space an organic flow by allowing each board to express a variety of wood grain patterns. Developed in collaboration with celebrated interior designer David Senise, this collection combines elements inspired by nature to bring thoughtful sophistication & grounded aesthetics from the natural world into commercial & residential spaces.

Engineered (Prefinished)



CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 30 — Engineered Wood Flooring
 09 64 29—Wood Strip and Plank Flooring
 06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks
 1180 Commercial Dr
 Farmington, NY 14425

MATERIALS

Product: Natural Expressions Collection Casual White Oak
 Collection: The Natural Expressions Collection
 Species: Domestic White Oak
 Core: 9-Ply FSC® Certified & TCSA Compliant Birch Plywood
 Texture: Smooth Planed
 Source: Sustainably Harvested Forests
 Color: Available in a range of finishes by inspired by Nature.
 Finish: UV Cured Hard-Wax Oil
 Hardness: 1360
(Janka Ball Test ASTM D143, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

DIMENSIONS & MILLING

Profile + End Match: **TGMBVE** (Tongue and Groove Micro-Bevel Edge)
 Thickness: 5/8"
 Width: 8" face
 Length: 18"—12' random

ADDITIONAL INFORMATION

Heartwood: No limitation on heartwood.
 Grain: No limitation on grain orientation.
 Knots: No limitations on sound knots.
 Texture: Surface should generally be 95% clear of saw marks or patina.
 Voids: In engineered prefinished product voids up to 1" in diameter will be filled with a black composite.
Insect marks, including pinholes, may also be present on the surface.
 Discoloration: Unlimited mineral staining is permitted.
 Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of the material increases.
 Moisture: Kiln dried 6–9% prior to milling.
 Content:

CERTIFICATIONS & LEED INFORMATION

FSC® Claim: FSC Mix Credit (GFA-COC-008489)
GREENGUARD Gold Certified
 MRc3: Low-Emmiting Materials (Greenguard Gold)
 MRc4: Building Product Selection and Procurement (FSC Mix Credit)

INSTALLATION RECOMMENDATIONS

Overage: **Minimum 10% additional material**
For on-site grading, trimming and installation factors.
 Climate: As with any wood flooring product, the room temperature should be held at a consistent range between 60-80° F with relative humidity between 30-60%.
Environmental conditions consistently outside of these parameters could result in product performance issues.





Shoji White

SKU# 27162114911



Hazelwood

SKU# 27162115011




Ginger Root

SKU# 27162115111




Toasted Wheat

SKU# 27162115211




Autumn Brown

SKU# 27162115311



Coffee Bean

SKU# 27162115411




Warm Umber

SKU# 27162115511




Toasted (Interior Use Only)

SKU# 27162115611




Driftwood

SKU# 27162115711




Nantucket Fog

SKU# 27162115811



Rain Cloud

SKU# 27162115911



Osaka Black

SKU# 27162116011