

Indonesian Teak—Colors of Indonesia



Pioneer millworks
RECLAIMED & SUSTAINABLE WOOD PRODUCTS



Colors of Indonesia is an incredibly durable, visually dynamic teak panel product made of Teak reclaimed from old fishing boats. Original paint colors abound—the Aqua Mix grade has a heavier mixture of light, deep, and bright blue tones along with greens, whites, pinks, and

natural surface colors. The Multicolor Mix grade has a mixture of maroon, deep red, soft reds with occasional whites, teals, and natural surface colors. Both materials come standard with a shiplap.



Pioneer Millworks Indonesian Teak—Colors of Indonesia

9/20/18

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks
1180 Commercial Drive
Farmington, NY 14425
Phone: 800-951-9663

Pioneer Millworks
2609 SE 6th Avenue
Portland, OR 97202
Phone: 503-719-4800

MATERIALS

1. **Product Name:** Teak Colors of Indonesia
2. **Species/Description:** Indonesian Teak with original patina
3. **Source:** Agricultural/Industrial deconstruction
4. **Color:** Paint remnants may range from blues to greens to white and may include some reds and browns and yellows. Unlimited color variation is inherent to the product.
5. **Grade:** Colors of Indonesia
6. **Dimensions:**
 - Solid**
TH—1/4"
WD—8"
LG—87"
 - Engineered**
TH—N.A.
WD—N.A.
LG—N.A.
7. **Milling:** Shiplap
8. **Finish:** Unfinished unless specified otherwise
9. **Hardness:** 1070
(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)
10. **FSC Claim: (SCS-COC-003998)**
Solid: Recycled 100%

ADDITIONAL INFORMATION

- Heartwood:** No restriction
Grain: No restriction
Knots: No limitations on sound knots, surface defects from chipped or open knots may be present.
Texture: This mixture shows a varied pattern of saw marks, wear patterns, colors and textures.
Overwood of up to 1/8" can be expected.
Voids: Nail, bolt and other mechanical holes can be present and occasionally reach 3/8" in diameter. Voids up to 2" in diameter may be filled with oval plugs.
Discoloration: Original paint remnants are present and may test positive for lead.
Checks: None allowed.
Moisture Content: Kiln dried 6–9% prior to milling.

LEED INFORMATION

- MRc3:** Materials Reuse (materials used for this credit cannot be applied to MRc4 or MRc5)
MRc4: Recycled Content, 100% Post-Consumer Recycled Content (materials used for this credit cannot be applied to MRc3 or MRc7)
MRc5: Regional Materials (call for details)
MRc7: Solid Materials are FSC Recycled 100%

RECOMMENDED COVERAGE

Recommend 7–12% additional material for on-site grading, trimming and installation factors.



Multicolor Mix



Aqua Mix



The mark of responsible forestry



Information is deemed reliable but subject to change. All photos for representation only. Additional information available at our website or call our wood design experts.