Sustainably Harvested—White Oak



Sourced from forests which are carefully managed according to strict Forest Stewardship Council® (FSC®) requirements, this high-grade White Oak offers a more uniform appearance than its reclaimed counterpart. Expect consistent color

tones ranging from cream to tan and a few small knots. This sustainably harvested wood pairs especially well with our custom eco-friendly finishes for floors and paneling.



Pioneer Millworks Sustainably Harvested—White Oak

CUT AND PASTE SPECIFICATION INTO APPROPRIATE CSI DIVISION

09 64 29—Wood strip and plank flooring 06 42 00—Wood Paneling

MANUFACTURER

Pioneer Millworks 1180 Commercial Drive Farmington, NY 14425 Phone: 800-951-9663

Pioneer Millworks 2609 SE 6th Avenue Portland, OR 97202 Phone: 503-719-4800

MATERIALS

- 1. Product Name: Sustainably Harvested White Oak
- 2. Species/Description: Domestic White Oak, smooth planed
- 3. **Source**: Sustainably Harvested Forests
- 4. Color: Tones may range from cream to tan. Unlimited color variation is inherent to the product.
- 5. Grade: Select and Better
- 6. Dimensions:

Solid

TH- 3/4"

WD— 3" to 10" as specified LG— 18" to 144" random

Engineered

TH— ½" or 5/8" as specified WD— 4" to 8" as specified LG— 12" to 96" random

- 7. Milling: Tongue and Groove Square Edge (TGSQE)
- 8. Finish: Unfinished unless specified otherwise
- 9. Hardness: 1260

(Janka Ball Test ASTM D1037-96A, Natural wood products have no minimum hardness since hardness is a characteristic of species and cannot be controlled)

10. FSC Claim: (SCS-COC-003998)

Solid: FSC 100%

Engineered: FSC Mix 70%

ADDITIONAL INFORMATION

Heartwood: 75% Heartwood

Grain: Clear

Knots: 90% free of knots. Existing knots to be no larger than ¼" diameter.

Texture: Surface should be 100% clear of saw marks.

Voids: No voids are permitted.

Discoloration: Limited mineral staining is permitted.

Checks: Structural checks not affecting the integrity of the plank, once installed, are allowed and more prevalent as the width of

the material increases.

Substrate: FSC Baltic Birch CPCP grade 9mm thickness for finished 1/2" 12mm thickness for finished 5/8"

No Urea Formaldehyde added (Note: wood has trace amounts naturally)

Glue: Formaldehyde-free low VOC glue

Moisture Content: Kiln dried 6-9% prior to milling.

LEED INFORMATION

MRc3: N.A. MRc4: N.A

MRc5: Regional Materials (call for details)

MRc7: Certified Wood: Solid FSC 100%; Engineered FSC Mix 70%

RECOMMENDED OVERAGE

Recommend 7-12% additional material for on-site grading, trimming and installation factors.



















Information is deemed reliable but subject to change, All photos for representation only. Additional information available at our website or call our wood design experts.